

TECNOSLIM / SINGLE-GLAZED PARTITION WALLS



TecnoSlim is the sleekest single-glazed wall in the range. Combined with light interior walls (plasterboard, Ytong, etc.) this is a rapid and economical choice that is a match for more expensive systems where comfort and aesthetics are concerned. The door frame may be used for either a solid or a glass door. Access control with an electrical opener is possible. The doors can be realised up to room height.

WALL THICKNESS	25 mm wide U sections. 55 mm frame			
GLASS TYPE (STANDARD NBN EN 1991-1-4)	HEIGHT	≤ 2.600 mm	≤ 3.100 mm	≤ 3.500 mm
	toughened	10	12	15
	laminated	66.2	88.2	88.2
MODULE TRANSITION	minimal glass-glass connection, various versions possible (alu, plexi, sealant,...)			
MODULE WIDTH	up to approx. 900 mm			
WALL HEIGHT	maximum approx. 3.200 mm			
VISIBLE SECTIONS	extruded aluminum, with powder coating or anodised			
CEILING SECTIONS	aluminum U-section: 35 x 25 x 35 mm			
FLOOR SECTIONS	aluminum U-section: 35 x 25 x 35 mm			
INSULATION	N/A			
DOOR FRAME	suitable for solid plain door or all-glass door			
OPTIONAL	electric opener, light switch next to door			
DOOR SECTIONS IN STOCK	plain anodised. White 90% gloss. Grey metallic RAL 9006 30% gloss			
SOUND INSULATION RW (ISO 717)	33 to 38 dB			
FIRE RESISTANCE	no rating			

TECNOSLIM / DETAILS

